

MATERIAL SAFETY DATA SHEET
(SIMILAR TO OSHA FORM 174)

N.A. = Not Applicable
Not Est. = Not Established
Prop. = Proprietary

SECTION 1 - MANUFACTURER / DISTRIBUTOR INFORMATION

Product Name: DURA-GLOSS Multi-Speed Buffable Floor Coating
Supplier's Name: National Chemical Laboratories of PA, Inc.
Supplier's Address: 401 N. 10th Street · Philadelphia PA 19123
HMIS Hazard Code: Health: 1 Flammability: 0 Reactivity: 0 Other: 0
Chemical Family: Floor Finish
D.O.T. Shipping Name: N/A

Product #: 2507
Emergency Phone #: CHEM-TEL (800) 255-3924
Chemical Name: Acrylic Latex Blend
Formula: N.A. Blended Product
Hazard Class: N/A **D.O.T. ID#:** N/A

SECTION 2 - HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS NUMBER	% Concentration Range	Hazard Ratings (TLV/PEL)
Diethylene Glycol Monomethyl Ether	111-77-3	PROP.	Not Est.

SECTION 3 - PHYSICAL DATA

Boiling Point (°F): 212
Vapor Pressure: = To Water
Vapor Density: = To Water
Solubility in Water: Disperses
Appearance: Opaque, White liquid
Odor: Characteristically Acrylic

Specific Gravity: 1.051
Evaporation Rate: = To Water

SECTION 4 - FIRE AND EXPLOSION DATA

Flash Point (°F): None to boiling (TOC)
Flammable Limits: N.A.
Unusual Fire & Explosion Hazards: Heated material may liberate toxic fumes. Wear self contained breathing apparatus.

SECTION 5 - HEALTH HAZARD DATA

Route(s) of Entry: Inhalation: No Skin: Yes Ingestion: Yes **Threshold Limit Value:** Not Est.
Effects of Overexposure: May cause skin and eye irritation. May be harmful if swallowed. Ingestion may cause severe gastric distress and blockage.
Emergency & First Aid Procedures: **For Eyes:** Flush eyes with water for at least fifteen minutes. Do not rub eyes. Seek medical attention. **For Skin:** Wash thoroughly with soap and water. If irritation persists seek medical attention. **If ingested:** Do not induce vomiting. Give water. Seek medical attention. Never give anything by mouth to an unconscious person.
Conditions Aggravated by Exposure: None

Listed Carcinogen, Mutagen, Teratogen (Ingredient, Source, Amount): None

SECTION 6 - REACTIVITY DATA

Stability: Stable
Conditions to Avoid: None
Incompatibility: Avoid contact with strong acids and oxidizers
Hazardous Decomposition Products: Carbon Oxides and Acrylates
Hazardous Polymerization: Will not occur

SECTION 7 - SPILL OR LEAK PROCEDURES

Steps to be taken if material is released or spilled: Recontainerize by mopping, wet vacuum, or using a suitable absorbent.
Waste disposal method: Follow local, state, and federal regulations.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not required
Ventilation: Local
Protective Gloves: Not required
Eye Protection: Goggles or safety glasses with side shields.
Other Protective Equipment: Not required

SECTION 9 - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store between 40°F and 120°F. Keep from freezing.
Other Precautions: Keep out of reach of children. For professional use only.

The information contained in this MSDS was obtained from current and reliable sources, however the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of this company, it is not responsible for loss, injury and expense arising out of the product's improper use. No warranty, expressed or inferred, regarding the product described in this MSDS shall be created or inferred by any statement in this MSDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use or disposal of this product which may be covered by this MSDS. The user is responsible for full compliance.

Date Prepared – 10/05/00 By: G.C.